



S-440-JS-300 -SS

Item Series : Sprague

[Request Quote](#) [1]

This contaminate-free hydraulic power unit uses the S-216-JS-() pump. The unit's components include an air filter, pressure regulator and lubricator (FRL), air shut-off valve, muffler, manifold, liquid bleed valve, air pressure gauge and liquid pressure gauge. The base is steel and has four mounting holes. All components in contact with the liquid being pumped are stainless steel.

Filter Air Inlet Port Threads - 3/8" NPT

Item Name	Non-Contaminating Power Units	Pump Maximum Output	33500
Pump Maximum Output	2310	Pressure [psi]	
Pressure [bar]		Pump Liquid Outlet-	NBS 9/16-18
Filter Air Inlet Port	3/8	Displacement Per Stroke	.092
Thread- NPT [inches]			
Shipping Weight [lbs.]	36	Shipping Weight [kgs.]	16.3
Length [inches]	23 7/16	Length [cm]	59.8
Width [inches]	11 7/16	Width [cm]	29.4
Height [inches]	12	Height [cm]	30.5

Source URL: <https://www.boighill.com/sprague/s-440-js-300-ss>

Links

[1] <https://www.boighill.com/contact?height=600&width=500&iframe=true&brand=Sprague&series=Sprague&category=&item=S-440-JS-300-SS>